

ALL·IN·WOOD

Care instructions

PAINTED SURFACES, TUVAN

Tuvan furniture is painted using an older painting technique, which enables the paint to provide an even covering but also gives a natural wood feeling. The surface becomes matt and gives a soft impression with intended patchiness.

With our painting technique, a piece of furniture that has sustained surface damage can be repaired. The easiest way to improve a painted surface is to paint over the entire surface where the damage has occurred. Sand the surface in the direction of the grain and apply our finished ground paint, finely sand over and finally apply our pigmented lacquer. Remember that a piece of furniture in solid wood that has been painted and then well used becomes more and more beautiful with the passage of time.

PAINTED SURFACES, SETTLER

Furniture in the Settler range is treated in order to endure high levels of use. The furniture is firstly stained and then lacquered with a double component, environment friendly lacquer. No maintenance is required since the resulting surface provides a high level of tolerance and resistance. For cleaning purposes one is able to use any of the milder cleaning products to be found in the average household.

OILED SURFACES

Pure wooden surfaces are oiled which gives a warm and soft impression with a high level of feeling for the wood. Our oil is based on boiled flax oil and environment friendly solvent. The oil is oxide in nature which requires a long drying process. An oiled piece of furniture must be regularly maintained and should be re-oiled as soon as the surface begins to appear dry. With proper maintenance an oiled surface will become more and more beautiful and use resistant with the passage of time. When you need to oil your furniture you should begin with a damp cloth and small amount of detergent. Tougher stains can be sanded away with a fine sandpaper or steel wool. Sand the entire surface. Let the surface dry properly before treatment. Oil generously with the type of oil that is described above and let it be properly absorbed. It is important to dry away the oil carefully after a few minutes in order to avoid blotches. Often it is advisable to repeat the process. In order to achieve an even finer result, one can sand the surface with a fine steel wool that has been moistened in oil, follow up by polishing the surface with a dry cloth.